



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 10 kgf/cm²**

Çalışma Sıcaklığı: -10 / +300 °C

Seçenekler:

SDNR (F-7471), Ayar Diskli



Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 10 kgf/cm²**

Working temperature: -10 / +300 °C

Variants:

SDNR (F-7471), Regulating Disc

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of		
Steam of 205°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
12 kgf/cm ²	12 kgf/cm ²	14 kgf/cm ²	21 kgf/cm ²	15,4 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Steel	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Steel	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Steel
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole		Weight
					Pitch	Number	Hole
750411	751201	50	220	155	120	4	19
750412	751202	65	270	175	140	4	19
750413	751203	80	300	185	150	8	19
750414	751204	100	350	210	175	8	19
750415	751205	125	420	250	210	8	23
750416	751206	150	490	280	240	8	23
750417	751207	200	570	330	290	12	23
750418	751208	250	740	400	355	12	25
750419	751209	300	840	445	400	16	25