



Uygulama:

Sıcak ve soğuk su sistemleri, asit ve alkali özelliği bulunmayan sıvı akışkanlar için sürğülü valf
Çalışma Basıncı: **maksimum 10 bar**
Çalışma Sıcaklığı: -10 / +205 °C

Diğer Seçenekler:

İndikatör, Tahliye Tapası, Dişli Kutusu, Elektrik Aktüatör



Application:

Gate valve for hot and cold water, non-acidic and non-flammable liquid fluids
Working pressure: **maximum 10 bars**
Working temperature: -10 / +205°C

Variants:

Indicator, Drain Plug, Gearbox, Electric Actuator

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Permissible Working Pressure Working Temperature			Hydraulic Test Pressure for Leak-Tightness of	
Steam of 200°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
7 kgf/cm ²	10 kgf/cm ²	14 kgf/cm ²	15,4 kgf/cm ²	21 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Steel	6	Volan / Handwheel	GG 25
2	Kapak / Bonnet	Cast Steel	7	Salmastra / Gland Packing	Graphite
3	Sürğü Burcu / Wedge Ring	RG 5	8	Salmastra Bileziği / Gland	RG 5
4	Disk / Disc	Special Brass	9	Conta / Gasket	Graphite
5	Mil / Stem	Special Brass			

ÖLÇÜLER / DIMENSIONS

IMPA	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Number	Hole	Weight KG
750901	50	200	155	120	4	19	17,1
750902	65	220	175	140	4	19	26,5
750903	80	230	185	150	8	19	31,5
750904	100	250	210	175	8	19	44,9
750905	125	270	250	210	8	23	63,2
750906	150	290	280	240	8	23	82,3
750907	200	310	330	290	12	23	130
750908	250	340	400	355	12	25	203
750909	300	380	445	400	16	25	291
750910	350	420	490	445	16	25	368
750911	400	480	560	510	16	27	507