



**Uygulama:**

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 16 kgf/cm<sup>2</sup>**

Çalışma Sıcaklığı: -10 / +205 °C

**Seçenekler:**

SDNR (F-7410), Ayar Diskli



**Application:**

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 16 kgf/cm<sup>2</sup>**

Working temperature: -10 / +205 °C

**Variants:**

SDNR (F-7410), Regulating Disc

**BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE**

Permissible Working Pressure Working Temperature			Hydraulic Test Pressure for Leak-Tightness of	
Steam of 205°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
16 kgf/cm <sup>2</sup>	16 kgf/cm <sup>2</sup>	22 kgf/cm <sup>2</sup>	33 kgf/cm <sup>2</sup>	24,2 kgf/cm <sup>2</sup>

**PARÇA LİSTESİ / PART LIST**

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Bronze	9	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Bronze	10	Altıgen Somun / Hexagon Nut	Stainless Steel
3	Disk / Disc	Bronze	11	Somun Pimi / Split Pin	Brass
4	Disk Somunu / Disc Nut	Bronze	12	Kilitleme Mekanizması / Lock Plate	Brass
5	Salmastra / Packing Gland	Brass	13	Disk Kilit Vidası / Disc Lock Washer	Brass
6	Salmastra Somunu / Gland Nut	Brass	14	Salmastra / Packing	Non Asbetos
7	Mil / Stem	Brass	15	Etiket / Name Plate	Brass
8	Makine Vidası / Machine Screw	Brass	16	Baskı Yüzeyi / Sit Ring	Bronze

**ÖLÇÜLER / DIMENSIONS**

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole			Weight KG
					Pitch	Number	Hole	
750151	751081	15	70	95	70	4	15	2,8
750152	751082	20	75	100	75	4	15	3,7
750153	751083	25	85	125	90	4	19	5,2
750154	751084	32	95	135	100	4	19	7
750155	751085	40	100	140	105	4	19	8,5