



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 16 kgf/cm²**

Çalışma Sıcaklığı: -10 / +205 °C

Seçenekler:

SDNR (F-7409), Ayar Diskli



Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 16 kgf/cm²**

Working temperature: -10 / +205 °C

Variants:

SDNR (F-7409), Regulating Disc

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Permissible Working Pressure		Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
Steam of 205°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)	
16 kgf/cm ²	16 kgf/cm ²	22 kgf/cm ²	33 kgf/cm ²	24,2 kgf/cm ²	

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Bronze	9	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Bronze	10	Altıgen Somun / Hexagon Nut	Stainless Steel
3	Disk / Disc	Bronze	11	Somun Pimi / Split Pin	Brass
4	Disk Somunu / Disc Nut	Bronze	12	Kilitleme Mekanizması / Lock Plate	Brass
5	Salmastra / Packing Gland	Brass	13	Disk Kilit Vidası / Disc Lock Washer	Brass
6	Salmastra Somunu / Gland Nut	Brass	14	Salmastra / Packing	Non Asbetos
7	Mil / Stem	Brass	15	Etiket / Name Plate	Brass
8	Makine Vidası / Machine Screw	Brass	16	Baskı Yüzeyi / Sit Ring	Bronze

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole			Weight KG
					Pitch	Number	Hole	
750141	751071	15	110	95	70	4	15	2,8
750142	751072	20	120	100	75	4	15	3,7
750143	751073	25	130	125	90	4	19	5,2
750144	751074	32	160	135	100	4	19	7
750145	751075	40	180	140	105	4	19	8,5