



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 5 kgf/cm²**

Çalışma Sıcaklığı: -10 / +230 °C

Seçenekler:

STOP (F-7306), SDNR (F-7354), Ayar Diskli

Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 5 kgf/cm²**

Working temperature: -10 / +230°C

Variants:

STOP (F-7306), SDNR (F-7354), Regulating Disc

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
5 kgf/cm ²	5 kgf/cm ²	7 kgf/cm ²	10,3 kgf/cm ²	7,7 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron / Ductile Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron / Ductile Iron	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Iron / Ductile Iron
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Flange Bolt Hole Hole	Weight KG
750216	751116	50	100	130	105	4	15	12,9
750217	751117	65	115	155	130	4	15	18,2
750218	751118	80	130	180	145	4	19	23,4
750219	751119	100	150	200	165	8	19	33,7
750220	751120	125	170	235	200	8	19	46,2
750221	751121	150	190	265	230	8	19	63,4
750222	751122	200	220	320	280	8	23	105
750223	751123	250	275	385	345	12	23	166
750224	751124	300	310	430	390	12	23	243
750225	751125	350	360	480	435	12	25	327
750226	751126	400	395	540	495	16	25	459