



### Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: maksimum 10 kgf/cm<sup>2</sup>

Çalışma Sıcaklığı: -10 / +230 °C

### Seçenekler:

STOP (F-7308), SDNR (F-7376), Ayar Diskli

### Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: maximum 10 kgf/cm<sup>2</sup>

Working temperature: -10 / +230 °C

### Variants:

STOP (F-7308), SDNR (F-7376), Regulating Disc

### BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
10 kgf/cm <sup>2</sup>	10 kgf/cm <sup>2</sup>	14 kgf/cm <sup>2</sup>	21 kgf/cm <sup>2</sup>	15,4 kgf/cm <sup>2</sup>

### PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron / Ductile Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron / Ductile Iron	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Iron / Ductile Iron
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

### ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Flange Bolt Hole Hole	Weight KG
750246	751141	50	120	155	120	4	19	18,2
750247	751142	65	130	175	140	4	19	25,4
750248	751143	80	140	185	150	8	19	27,4
750249	751144	100	160	210	175	8	19	40,6
750250	751145	125	180	250	210	8	23	69,9
750251	751146	150	205	280	240	8	23	81
750252	751147	200	230	330	290	12	23	125
750253	751148	250	290	400	355	12	25	211
750254	751149	300	320	445	400	16	25	293