



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: maksimum 10 kgf/cm²

Çalışma Sıcaklığı: -10 / +230 °C

Seçenekler:

STOP (F-7307), SDNR (F-7375), Ayar Diskli

Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: maximum 10 kgf/cm²

Working temperature: -10 / +230 °C

Variants:

STOP (F-7307), SDNR (F-7375), Regulating Disc

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
10 kgf/cm ²	10 kgf/cm ²	14 kgf/cm ²	21 kgf/cm ²	15,4 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron / Ductile Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron / Ductile Iron	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Iron / Ductile Iron
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Flange Bolt Hole Hole	Weight KG
750231	751131	50	220	155	120	4	19	19,9
750232	751132	65	270	175	140	4	19	28,7
750233	751133	80	300	185	150	8	19	32,4
750234	751134	100	350	210	175	8	19	48,7
750235	751135	125	420	250	210	8	23	73,1
750236	751136	150	490	280	240	8	23	104
750237	751137	200	570	330	290	12	23	162
750238	751138	250	740	400	355	12	25	304
750239	751139	300	840	445	400	16	25	458