



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: maksimum 16 kgf/cm²

Çalışma Sıcaklığı: -10 / +230 °C

Seçenekler:

STOP (F-7309), SDNR (F-7377), Ayar Diskli

Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: maximum 16 kgf/cm²

Working temperature: -10 / +230 °C

Variants:

STOP (F-7309), SDNR (F-7377), Regulating Disc

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
16 kgf/cm ²	16 kgf/cm ²	22 kgf/cm ²	33 kgf/cm ²	24,2 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron / Ductile Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron / Ductile Iron	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Iron / Ductile Iron
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

ÖLÇÜLER / DIMENSIONS

IMPA	IMPA	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Weight KG
STOP	SDNR						
750261	751151	50	220	155	120	8	19,6
750262	751152	65	270	175	140	8	28,3
750263	751153	80	300	200	160	8	40,4
750264	751154	100	350	225	185	8	56,9
750265	751155	125	420	270	225	8	89,5
750266	751156	150	490	305	260	12	123
750267	751157	200	570	350	305	12	188