



**Uygulama:**

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 5 kgf/cm<sup>2</sup>**

Çalışma Sıcaklığı: -10 / +230 °C

**Seçenekler:**

STOP (F-7305), SDNR (F-7353), Ayar Diskli

**Application:**

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 5 kgf/cm<sup>2</sup>**

Working temperature: -10 / +230°C

**Variants:**

STOP (F-7305), SDNR (F-7353), Regulating Disc

**BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE**

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
5 kgf/cm <sup>2</sup>	5 kgf/cm <sup>2</sup>	7 kgf/cm <sup>2</sup>	10,3 kgf/cm <sup>2</sup>	7,7 kgf/cm <sup>2</sup>

**PARÇA LİSTESİ / PART LIST**

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron / Ductile Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron / Ductile Iron	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	Stainless Steel	8	Salmastra Baskısı / Gland	Cast Iron / Ductile Iron
4	Disk / Disc	Stainless Steel	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Stainless Steel	10	Civata – Somun / Bolt – Nut	Stainless Steel

**ÖLÇÜLER / DIMENSIONS**

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Weight KG
750201	751101	50	210	130	105	4	14,7
750202	751102	65	250	155	130	4	21,3
750203	751103	80	280	180	145	4	27,7
750204	751104	100	340	200	165	8	40,8
750205	751105	125	410	235	200	8	57,6
750206	751106	150	480	265	230	8	80,3
750207	751107	200	570	320	280	8	139
750208	751108	250	740	385	345	12	216
750209	751109	300	840	430	390	12	346
750210	751110	350	940	480	435	12	418
750211	751111	400	1050	540	495	16	600