



Uygulama:

Buhar, gazlar ve sıvılar için emniyet valfi

Çalışma Basıncı (Giriş) **maks. 16 bar**

min. 0,2 bar

Çalışma Sıcaklığı **-10 / +180 °C**

Tam Tahliye Basıncı **ayar basıncı +% 10**

Tekrar Kapatma Basıncı **ayar basıncı -%10 gazda, -%20 sıvıda**

Dizayn:

PN 10/16, Flanş bağlantılı

Açılı tip, Oransal kalkışlı, Yaylı

Diğer Seçenekler:

PTFE Sit, Viton Sit

Application:

Safety valve for steam, gases and liquids

Working (inlet) pressure: **max. 16 bars**

min. 0,2 bars

Working temperature: **-10 / +180°C**

Overpressure **set pressure +% 20 in gases and liquids**

Reclose Pressure **set pres. -%10 in gases, -%20 in liquids**

Design:

PN 10/16 Flanged connection

Angle type, Nprmal lift, Spring loaded

Variants:

PTFE Seat, Viton Seat



PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde (Body)	GG 25
2	Kapak (Cap)	GG 25
3	Üst Kapak (Hood)	GG 25
4	Sabitleme Diski (Fixing Disc)	Stainless Steel
5	Yay Baskısı (Spring Press)	Stainless Steel
6	Mil Kılavuzu (Shaft Pin)	Stainless Steel
7	Sit (Seating)	Stainless Steel
8	Klape (Disc)	Stainless Steel
9	Klape Rakoru (Shaft Connector)	Stainless Steel
10	Mil (Shaft)	Stainless Steel
11	Yay (Spring)	Steel
12	Ayarlama Vidası (Hollow Screw)	Steel
13	Kilitleme Somunu (Hollow Screw Nut)	Steel
14	Kaldırma Çatalı (Cam)	Steel
15	Kol (Lever)	Steel

ÖLÇÜLER / DIMENSIONS

DN	25	32	40	50	65	80	100
H	383	402	413	430	519	584	636
S1	100	105	115	125	145	155	175
S	100	105	115	125	145	155	175
dg	25	32	40	50	65	80	100
Dg	115	140	150	165	185	200	220
dç	25	32	40	50	65	80	100
Dç	115	140	150	165	185	200	220
kg	10	12	14	17	27	30	48